

报告编号: 202009-217

检索报告


项目名称: 论文被 EI 收录情况证明

委托人: 西南大学 柑桔研究所 王珺

日期: 2020 年 9 月 23 日

认证单位: 教育部科技查新工作站 N08

二〇二〇年制

检索项目名称	委托人王珺提交论文被 EI 收录情况			
查新机构	名称	教育部科技查新工作站 N08	邮编	400715
	地址	重庆市北碚区西南大学图书馆	电话	023-68253283
委托文献目录	1.Optimization of microwave heating on orange sacs products (Open Access) Wang, Jun (National Citrus Engineering Research Center, Chongqing; 410125, China); Wang, Jun; Li, Guijie; Li, Guijie; Cheng, Yujiao; Cheng, Yujiao; Huang, Linhua; Huang, Linhua; Sun, Rongrong; Sun, Rongrong; Wu, Houjiu; Wu, Houjiu Source: IOP Conference Series: Earth and Environmental Science, v 512, n 1, June 17, 2020, 2020 4th International Workshop on Advances in Energy Science and Environment Engineering			
	2.Effect of Peeling Method on the Volatile Flavor of Citrus Fruit (Open Access) Wang, Jun (National Citrus Engineering Research Center, Chongqing; 410125, China); Cheng, Yujiao; Huang, Linhua; Wu, Houjiu; Sun, Rongrong; Li, Guijie Source: IOP Conference Series: Earth and Environmental Science, v 474, n 3, May 14, 2020, 2nd International Conference on Environmental Prevention and Pollution Control Technologies - 2. Agricultural Engineering and Information Technology			
检索的数据库范围	1. EI(https://www.engineeringvillage.com/)—2000 年至今			
检索结论	<p>经检索, 王珺提交的 2 篇论文(第一作者)被 EI 收录;检索结果详细情况见附件 1 和附件 2。</p> <div style="display: flex; justify-content: space-between; align-items: center;"> <div style="text-align: center;">  <p>检索人(签名): 周剑</p> </div> <div style="text-align: center;"> <p>职称: 研究馆员</p> <p>教育部科技查新工作站 N08</p> <p>2020 年 9 月 23 日</p> </div> </div>			
备注	1、影响因子及分区为论文发表当年或当前最新的影响因子和分区。			

附件 1: EI 收录情况

题名	检索号	文献类型	会议地点	出版时间
1.Optimization of microwave heating on orange sacs products (Open Access) Wang, Jun (National Citrus Engineering Research Center, Chongqing; 410125, China); Wang, Jun; Li, Guijie; Li, Guijie; Cheng, Yujiao; Cheng, Yujiao; Huang, Linhua; Huang, Linhua; Sun, Rongrong; Sun, Rongrong; Wu, Houjiu; Wu, Houjiu Source: IOP Conference Series: Earth and Environmental Science, v 512, n 1, June 17, 2020, 2020 4th International Workshop on Advances in Energy Science and Environment Engineering	20202808927276	会议论文	Hangzhou, China	2020
2.Effect of Peeling Method on the Volatile Flavor of Citrus Fruit (Open Access) Wang, Jun (National Citrus Engineering Research Center, Chongqing; 410125, China); Cheng, Yujiao; Huang, Linhua; Wu, Houjiu; Sun, Rongrong; Li, Guijie Source: IOP Conference Series: Earth and Environmental Science, v 474, n 3, May 14, 2020, 2nd International Conference on Environmental Prevention and Pollution Control Technologies - 2. Agricultural Engineering and Information Technology	20202208765069	会议论文	Sanya, China	2020

附件 2:

<RECORD 1>

Accession number:20202808927276

Title:Optimization of microwave heating on orange sacs products (Open Access)

Authors:Wang, Jun (1); Wang, Jun (2); Li, Guijie (1); Li, Guijie (2); Cheng, Yujiao (1); Cheng, Yujiao (2); Huang, Linhua (1); Huang, Linhua (2); Sun, Rongrong (1); Sun, Rongrong (2); Wu, Houjiu (1); Wu, Houjiu (2)

Author affiliation:(1) National Citrus Engineering Research Center, Chongqing; 410125, China; (2) Citrus Research Institute, Southwest University, Chongqing; 400712, China

Corresponding author:Wu, Houjiu(wuhoujiu@cric.cn)

Source title:IOP Conference Series: Earth and Environmental Science

Abbreviated source title:IOP Conf. Ser. Earth Environ. Sci.

Volume:512

Part number:1 of 1

Issue:1

Issue title:2020 4th International Workshop on Advances in Energy Science and Environment Engineering

Issue date: June 17, 2020
Publication year: 2020
Article number: 012070
Language: English
ISSN: 17551307
E-ISSN: 17551315
Document type: Conference article (CA)
Conference name: 2020 4th International Workshop on Advances in Energy Science and Environment Engineering, AESEE 2020
Conference date: April 10, 2020 - April 12, 2020
Conference location: Hangzhou, China
Conference code: 161364
Publisher: Institute of Physics Publishing
Number of references: 14
Main heading: Microwaves
Controlled terms: Citrus fruits - Food processing - Microwave heating - Sterilization (cleaning) - Surface properties
Uncontrolled terms: Material quantities - Microwave assisted - Microwave sterilization - Optimal processing - Response surface - Response surface methodology - Thermal sterilization - Vegetable products
Classification code: 711 Electromagnetic Waves - 711.1 Electromagnetic Waves in Different Media - 821.4 Agricultural Products - 822.2 Food Processing Operations - 951 Materials Science
Numerical data indexing: Mass 4.50e+00kg, Power 6.00e+03W, Time 3.50e+02s
DOI: 10.1088/1755-1315/512/1/012070
Funding details: Number: 4411901868, Acronym: -, Sponsor: -; Number: 2017YFD0400701, Acronym: -, Sponsor: Jilin Province Key R&D Plan Project;
Funding text: This research was supported by National Key R&D Plan (2017YFD0400701) and School Local Cooperation Project (4411901868), China.

<RECORD 2>

Accession number: 20202208765069
Title: Effect of Peeling Method on the Volatile Flavor of Citrus Fruit (Open Access)
Authors: Wang, Jun (1, 2); Cheng, Yujiao (1, 2); Huang, Linhua (1, 2); Wu, Houjiu (1, 2); Sun, Rongrong (1, 2); Li, Guijie (1, 2)
Author affiliation: (1) National Citrus Engineering Research Center, Chongqing; 410125, China; (2) Citrus Research Institute, Southwest University, Chongqing; 400712, China
Corresponding author: Wang, Jun (liguijie@cric.cn)
Source title: IOP Conference Series: Earth and Environmental Science
Abbreviated source title: IOP Conf. Ser. Earth Environ. Sci.
Volume: 474
Part number: 3 of 7
Issue: 3
Issue title: 2nd International Conference on Environmental Prevention and Pollution Control Technologies - 2. Agricultural Engineering and Information Technology

Issue date:May 14, 2020

Publication year:2020

Article number:032042

Language:English

ISSN:17551307

E-ISSN:17551315

Document type:Conference article (CA)

Conference name:2nd International Conference on Environmental Prevention and Pollution Control Technologies, EPPCT 2020

Conference date:January 10, 2020 - January 12, 2020

Conference location:Sanya, China

Conference code:160096

Publisher:Institute of Physics Publishing

Conventional (artificial) peeling method was used detection oxidation of limonene, (E)-2-hexenal flavor, ethyl hexanoate, hexyl butyrate flavor. © 2020 IOP Publishing Ltd. All rights reserved.

Number of references:9

Main heading:Pollution control

Controlled terms:Citrus fruits - Environmental technology - Essential oils - Gas chromatography - Mass spectrometry - Monoterpenes

Uncontrolled terms:Alpha-pinenes - Aromatic components - Enzymatic peeling - Ethyl butyrate - Ethyl esters - Ethyl hexanoate - Gas chromatography-mass spectrometry - Solid phase micro extraction

Classification code:454 Environmental Engineering - 801 Chemistry - 802.3 Chemical Operations - 804.1 Organic Compounds - 821.4 Agricultural Products

Numerical data indexing:Percentage 1.01e+00% to 1.02e+00%, Percentage 2.50e-01% to 5.00e-01%, Percentage 2.70e-01% to 3.50e-01%, Percentage 2.80e-01% to 2.59e+00%, Percentage 2.90e-01% to 1.86e+00%, Percentage 4.70e-01% to 7.30e-01%, Percentage 5.39e+00%, Percentage 6.93e+01% to 7.89e+01%, Percentage 7.00e-01% to 2.16e+00%, Percentage 7.00e-02% to 2.50e-01%, Percentage 7.50e-01% to 1.10e+00%, Percentage 8.14e+00% to 1.30e+01%

DOI:10.1088/1755-1315/474/3/032042

Funding details: Number: NCERC20119004, Acronym: -, Sponsor: -;Number: KJQN201801613, Acronym: -, Sponsor: -;Number: 4411901868, Acronym: -, Sponsor: -;Number: 2017YFD0400701, Acronym: -, Sponsor: Jilin Province Key R&D Plan Project;

Funding text:This research was supported by Open Project of National Citrus Engineering Technology Research Center (NCERC20119004), National Key R&D Plan (2017YFD0400701), School Local Cooperation Project (4411901868), Science and Technology Research Project of Chongqing Education Commission (KJQN201801613), China.

Database:Compendex

Compilation and indexing terms, Copyright 2020 Elsevier Inc.

PAPER • OPEN ACCESS

Optimization of microwave heating on orange sacs products

To cite this article: Jun Wang *et al* 2020 *IOP Conf. Ser.: Earth Environ. Sci.* **512** 012070

View the [article online](#) for updates and enhancements.

Optimization of microwave heating on orange sacs products

Jun Wang^{1,2}, Guijie Li^{1,2}, Yujiao Cheng^{1,2}, Linhua Huang^{1,2}, Rongrong Sun^{1,2}, and Houjiu Wu^{1,2,*}

¹National Citrus Engineering Research Center, Chongqing 410125, China

²Citrus research institute, Southwest University, Chongqing 400712, China

* Corresponding author: wuhoujiu@cric.cn

Abstract. Various applications of microwave have been put into effect in the field of food processing. The microwave assisted thermal sterilization (MATS) was of great significance because of its less time consuming and higher efficient. In this paper, response surface methodology was used to optimize the process. The sterilization of orange sacs was potimized using by response surface methodology (RSM). The optimal processing parameters of MATS on orange sacs are as follow: microwave power, 6 kW, microwave sterilization time, 350 s, amount of orange sacs, 4500 g. Sterilized under this condition by MATS, orange sacs only maintained 3.7 CFU lethal magnitude which was consistent with the standards requirement. The key factor in the response surface using microwave sterilization and the interaction between them were also determined and discussed which could make it evident that MATS should be an idea candidate in the sterilization of some fruit or vegetable products as ready to eat. From these results, the best conditions of microwave sterilization are power 6kw, microwave sterilization time 350s and material quantity 4500g.

1. Introduction

Orange juice is sweet and sour, rich in flavor, and rich in vitamin C, carotene and other nutrients, which is deeply loved by consumers [1-2]. At present, the key to the popular orange juice beverage in the market is the suspension of juice cells. Generally, juice cells are required to be full, uniform in size, bright in color and rich in vitamin C. However, in the process of industrial production, storage and transportation, juice cells are easy to be polluted by microorganisms, resulting in spoilage [3-4]. Therefore, it is particularly important to find a bactericidal technology that can control the growth and reproduction of microorganisms, and reduce the spoilage and deterioration of juice cell quality.

At present, orange juice often uses thermal sterilization technology (pasteurization and high temperature instantaneous sterilization) [5-6]. Pasteurization temperature is too low, so the sterilization effect is not ideal; high temperature instantaneous sterilization can achieve better sterilization effect, but it will lead to excessive loss of nutritional quality of fruit juice. In recent years, there are more and more ways different from traditional sterilization, such as microwave sterilization, ultra-high pressure sterilization, pulse electric field sterilization, UV sterilization and so on [7-9]. Microwave technology can reduce the number of microorganisms in fruit juice, but also maintain the nutrition, flavor and safety quality of the product. It has achieved good results in apple juice, grapefruit juice, blueberry juice and other fruit juice sterilization [10-14].

In this study, microwave sterilization was used to treat juice cells in bags, and the best way of sterilization was selected. At the same time, the nutritional quality of navel orange and summer orange



juice cells after microwave sterilization was evaluated in order to provide scientific guidance for the application of microwave sterilization technology in juice cell sterilization.

The process optimization of microwave heating orange sacs products had not been studied. This research is based on the laboratory experiments, the factory research is needed in the future

2. Methods

2.1. Preparation of juice cells of navel orange and sweet orange

Fruit washing → Enzyme treatment, peeling, whole fruit ball rinsing → Juice cell separation with juice cell disperser → Removal of damaged capsule, seeds and other sundries → Juice cell filtration with 20 mesh sieve of JBT pulp tester → Juice cell and fresh fruit juice 6:4 mixing, packaging and sealing with high temperature resistant cooking bags, 200 ± 5 g per bag.

2.2 Single factor test design

For navel orange juice cells, the microwave power was 6 kW, the sterilization time was 150 s, and the material quantity is 3500 g. The effects of microwave power (3, 6, 9 kW), sterilization time (50, 100, 150, 200, 250, 350 s), and material quantity (1500, 2500, 3500, 4500, 5500 g) on the germicidal efficacy of navel orange juice cells were investigated

2.3 Response surface test optimization of microwave sterilization process

According to the design principle of box Behnken test and the results of single factor test, three factors, namely microwave power, sterilization time and material quantity, were taken as independent variables, and the order of magnitude y (Formula 1) with the total number of colonies reduced was taken as the response value to design the test. See Table 1 for test factors and level design. Formula 1 was $Y = -\lg(N/N_0)$, in the formula: Y was the order of magnitude of the reduction of the total number of colonies; N was the total number of bacteria in 1 mL juice after microwave treatment; N_0 was the total number of bacteria in 1 mL juice of the control group.

Table 1. Response surface test factor level table.

Factor	Code	Coding level		
		-1	0	1
Power (kW)	X_1	3	6	9
Time (s)	X_2	150	250	350
Sacs weight (g)	X_3	2500	3500	4500

2.4 Microbiological determination

Take the sterilized sample into 5, 10, 20 times test tube for dilution, take 1 mL sample to 3m test piece, cover the surface film and press it gently with finger pressure plate. Three parallel experiments were conducted for each treatment. The total number of colonies was cultured in 37°C constant temperature incubator for 48 h, and the control group was used as the control group. Take out the test group and the control group, count and record, and finally calculate the sterilization rate. Sterilization rate (%) = (number of control group - number of experiment group)/number of control group $\times 100$.

2.5 Determination of soluble solid content (SSC), total acid (TA), vitamin C (Vc)

SSC was determined by hand-held saccharometer, and TA was determined by acid-base titration, and Vc was determined by 2, 6- two chlorophenol indophenol titration.

2.6 Hardness measurement

The hardness of orange juice cell was measured by texture analyzer. The parameters were: TPA measurement mode, P/0.5 down pressure probe. The speed before measurement was 5 mm/s, and the

speed after measurement was 1 mm/s, meanwhile the speed after measurement was 5 mm/s, the compression rate was 30%, and the initiating force was 5 g.

2.7 Color difference measurement

The color of juice cells was measured by color i5 colorimeter. The juice cells of each variety were measured 10 times, and the average value was taken. Chroma measurement was mainly based on CIE L^* , a^* , b^* color standards, respectively, to determine L^* , a^* , b^* values of juice cells.

2.8 Statistical analysis of data

Using the software of origin 8.0 and SPSS13.0, the one-way ANOVA and Duncan multiple comparison were carried out, and the significance level was 0.05.

3. Results and discussion

3.1 Microwave sterilization of navel orange juice sacs

3.1.1 Influence of microwave power on sterilization rate

The fixed sterilization time was 150 s, the material quantity was 3500g, the range of sterilization power was 3, 4.5, 6, 7.5 and 9 kW, and the better power was selected with the sterilization rate as the index. It could be seen from Fig. 1 that with the increase of microwave power, the number of colonies in the juice cell showed a downward trend, and the sterilization rate has increased significantly. When the microwave power was 6kW, the sterilization rate reached 97.50%, which was significantly different from the microwave power of 3.0 kW, 4.5 kW, 9 kW treatment group ($P < 0.01$), but not significantly different from the 7.5 kW treatment group ($P > 0.05$). In addition, there was no significant difference between the 7.5 kW treatment group and 9 kW treatment group ($P > 0.05$). Considering the comprehensive energy consumption, it was suitable to choose the microwave power of 6 kW.




Fig. 1. Effects of microwave power on sterilization rate.

3.1.2 Influence of microwave time on sterilization rate

Microwave sterilization equipment determines the processing time through the rotation speed of the conveyor belt, and the rotation speed is related to the processing time. Fixed sterilization power 6 kW, sacs weight 3500 g, microwave time range of 50, 100, 150, 250 and 350 s, with sterilization rate as the index to choose the better time. It could be seen from Fig. 2 that with the increase of microwave time, the number of colonies in the juice cell showed a downward trend, and the sterilization rate showed an upward trend. When the microwave time was 50, 100, 150, 250 and 350 seconds, the sterilization rate was 96.5%, 97.0%, 98.22%, 99.5% and 99.6% respectively. The difference of sterilization time between 250 s treatment group and 50s, 100s and 150 s treatment group was very significant ($P < 0.01$), but not between 350 s treatment group and 250 s treatment group ($P > 0.05$). According to the comprehensive sterilization efficiency and energy consumption ratio, 250 s was the best microwave treatment time.




Fig. 2. Effects of microwave power on sterilization rate.

3.1.3 Influence of sacs weight on sterilization rate

In microwave sterilization, the sacs weight determines the microwave absorption efficiency. Fix the sterilization power 6 kW, time 250 s, and set the range of sacs weight 1500, 2500, 3500, 4500 and 5500 g; meanwhile select the better sacs weight with sterilization rate as the index. As shown in Fig. 3, with the increase of sacs weight, the sterilization rate showed an upward trend. When the sacs weight was 1500, 2500, 3500, 4500 and 5500 g, and the sterilization rate was 99.96%, 97.94%, 99.47%, 98.18% and 97.33% respectively. In addition to 1500 g treatment group, the difference between 2500 g treatment group and each treatment group was very significant ($P < 0.01$). Considering working efficiency, energy consumption and other factors, 3500 g was the better sacs weight.

3.2 Model establishment and significance test

Using the software of design expert 7.1.6 to fit the test data of Table 2, we can see that the quadratic multiple regression model equation of the reduction of the total number of colonies of orange juice after microwave treatment to the independent variable microwave power, temperature and sterilization time was $Y = 3.59 + 0.37 \times 1 + 0.35 \times 2 + 0.16 \times 3 + 0.023 \times 1 \times 2 + 0.11 \times 1 \times 3 + 0.020 \times 2 \times 3 - 0.45 \times 1^2 - 0.16 \times 2^2 - 0.22 \times 3^2$. Table 3 was the variance analysis of the model, and table 4 was the significance test of the model coefficient.




Fig. 3. Effects of sacs weight on sterilization rate.

It could be seen from Table 3 that $F = 37.32 > F_{0.01}(9,4) = 14.66$, $P < 0.0001$, indicating that the model was extremely significant, and the difference between different treatments is extremely significant. $F = 6.3 < F_{0.05}(9,3) = 8.81$, missing item $P = 0.0537 > 0.05$, the difference was not significant, which showed that the residual error is caused by random error. The correction decision coefficient of the model $R^2_{Adj} = 0.9533$, which shows that 95.33% of the response value can be explained by the model, only 4.67% of the variation can not be explained, further indicating that the model fitting is good, the

test error is small, and the model can be used to analyze and predict the order of magnitude of the reduction of the total bacterial count of the juice cells after microwave treatment.

It could be seen from the significance test of regression equation coefficient in Table 4 that the first term X_1 ($P < 0.0001$), X_2 ($P < 0.0001$), X_3 ($P < 0.0001$), the second term X_{12} ($P < 0.0001$), X_{32} ($P = 0.0037$) of model equation are extremely significant; the second term X_{22} ($P = 0.0145$) is significant, and the interaction terms are not significant.

Table 2. Factors, levels, and results of response surface tests.

No.	Coding level			Response value
	X_1	X_2	X_3	
1	1	-1	0	2.92
2	1	1	0	3.70
3	-1	1	0	3.07
4	0	0	0	3.55
5	0	0	0	3.64
6	1	0	-1	3.02
7	0	-1	1	3.02
8	0	1	-1	3.36
9	0	0	0	3.6
10	-1	0	1	2.6
11	0	0	0	3.64
12	1	0	1	3.64
13	0	1	1	3.62
14	0	-1	-1	2.84
15	-1	-1	0	2.2
16	0	0	0	3.51
17	-1	0	-1	2.42

Table 3. Analysis of variance of the developed regression model.

Variation source	Sum of squares	Freedom	Mean square	F value	P value	Saliency
Model	3.59	9	0.40	37.32	< 0.0001	**
Residual	0.075	7	0.011	/	/	/
Missing item	0.062	3	0.021	6.30	0.0537	/
Pure error	0.013	4	0.00327	/	/	/
Sum	3.67	16	/	/	/	/
/	/	/	$R^2=0.9796$	$R^2_{Adj}=0.9533$	/	/

Table 4. Significance test of regression coefficients of the developed regression model.

Coefficient term	Regression coefficient	Freedom	Standard error	Lower confidence limit	Upper confidence limit	P value
Constant term	3.59	1	0.046	3.48	3.70	/
X_1	0.37	1	0.037	0.29	0.46	< 0.0001
X_2	0.35	1	0.037	0.26	0.43	< 0.0001
X_3	0.16	1	0.037	0.069	0.24	0.0038
X_1X_2	-0.023	1	0.052	-0.14	0.100	0.6766
X_1X_3	0.11	1	0.052	-0.012	0.23	0.0710
X_2X_3	0.020	1	0.052	-0.10	0.14	0.7105
X_1^2	-0.45	1	0.050	-0.57	-0.33	< 0.0001
X_2^2	-0.16	1	0.050	-0.28	-0.044	0.0145
X_3^2	-0.22	1	0.050	-0.33	-0.096	0.0037

In order to judge the contribution rate of the primary term, interactive term and secondary term of each factor to the sterilization effect, it is suitable to compare the contribution rate of each factor. The size of each factor is shown in Table 5. It can be seen that the leading effect of the equation is the microwave power, the primary time effect and the secondary power effect. The effect of the three test factors is $X_1 > X_2 > X_3$.

Table 5. Contribution rates of various factors.

Factor	Sum of squares	Freedom	Contribution rate (%)
x_1	1.120	1	31.517
x_2	0.960	1	27.015
x_3	0.190	1	5.347
x_1x_2	0.002	1	0.057
x_1x_3	0.048	1	1.351
x_2x_3	0.002	1	0.045
x_1^2	0.860	1	24.201
x_2^2	0.110	1	3.095
x_3^2	0.200	1	5.628
Missing item	0.062	3	0.017
Pure error	0.013	4	0.004

3.3 Contour and response surface analysis of microorganism response value of navel orange sacs treated by microwave

The response surface and contour map of the model equation were shown in Fig. 4, 5 and 6. The microwave sterilization conditions of juice cells were optimized by reducing about 3.5 orders of magnitude. As shown in Fig. 4, when the amount of material was 3500 g, the interaction effect of microwave power and microwave time on the number of colony death was significant. In the range of microwave power 4.59-9 kW and microwave sterilization time 207.59-350 s, the total number of colonies was 3.50. And in a certain range, with the increase of microwave power, the death order of the total number of colonies in the juice cell increased sharply, and the increasing trend was more significant than that caused by the extension of microwave sterilization time. When the microwave power was lower than 7.36 kW, and the number of colony death decreases with the decrease of microwave sterilization time.




Fig. 4. Response surface plot and its contour plot showing the effects of microwave power, treatment time and their mutual interactions on total viable count reduction of Orange juice sacs after sterilization.

Fig. 5 showed that when the microwave time was 250 s, the interaction effect of microwave power and orange sacs on the death level of the total number of colonies was significant. In the range of microwave power 5.33-9 kW and orange sacs weight 2961.93-4500 g, the death level of the total number of colonies could reach 3.50 or above. When the microwave power was at 7.09 kW, the amount of material was in the range of 2961.93-3442.61 g, and the death order of the total number of colonies decreases with the increase of the amount of orange sacs.

As shown in Fig. 6, when the microwave power is 6 kW, within the microwave sterilization time of 221.82–350 s and the orange sacs of 2707.81–4500 g, the death level of the total number of colonies was 3.50. When the orange sacs weight was fixed in the range of 2708.81–4500 g, with the increase of microwave sterilization time, the total number of colonies would be increased. When microwave sterilization time was fixed at 221.82–350 s, and the amount of orange sacs increased from 38779.26 g to 38779.26 g, which would lead to the death of the total number of colonies, and then gradually decreased.




Fig. 5. Response surface plot and its contour plot showing the effects of microwave power, weight quantity and their mutual interactions on total viable count reduction of Orange juice sacs after sterilization.




Fig. 6. Response surface plot and its contour plot showing the effects of microwave power, treatment time and their mutual interactions on total viable count reduction of Orange juice sacs after sterilization.

3.4 Model validation

The optimal conditions of microwave sterilization of orange juice cells were obtained by the software design expert 7.1.6. When the microwave power was 6 kW, the time of microwave sterilization was 350 s, and the amount of materials was 4500 g, the death level of the total number of colonies reached 3.73. In order to verify the validity of the model, 5 groups of model validation experiments were conducted with response value of 3.73, and the results were shown in Table 6. The results showed that the relative error between the measured value and the predicted value was less than 2%, which proves that the key factor of optimizing the technological parameters of microwave sterilization of orange sacs by response surface was feasible. By using design expert and response surface method (RSM), the second multiple mathematical model of microwave sterilization of orange sacs was established, which was proved to be reasonable and reliable. At the same time, the key factors and interaction of shadow microwave sterilization were discussed by using the response surface and its contour lines of the model, and the process parameters of killing 3.77 order of magnitude colonies were optimized. They are microwave power 8 kW, microwave sterilization time 324 s and orange sacs 3200 g.

Table 6. Validity verification of the developed regression model.

Experiment group	Factor			Response value		Relative error (%)
	x_1/kw	x_2/s	x_3/g	Measured	Forecast	
1	6	350	4500	3.71	3.73	0.53%
2	6	350	4500	3.77	3.73	1.33%
3	6	350	4500	3.75	3.73	0.53%
4	6	350	4500	3.76	3.73	0.80%
5	6	350	4500	3.74	3.73	0.37%

3.5 Comparison of nutritional indexes of navel orange sacs and summer orange juice cells treated by the best microwave processing parameters

As shown in Table 7, under the best technological conditions, microwave sterilization could reduce the nutritional quality of juice cells. There was no significant difference in the effect on SSC and TA ($P>0.05$); the loss rate of Vc was the most serious, which was 16.4-18%, which was mainly related to the degradation of Vc caused by the thermal effect of microwave sterilization. The increase of hardness index was related to citrus varieties, for example, there was significant difference before and after sterilization ($P<0.05$). There was no significant difference before and after sterilization ($P>0.05$). Microwave sterilization also had a certain effect on the color of juice cells. The values of L^* and B^* were increased, a^* is slightly decreased, and L^* of summer orange is larger, with better brightness; a^* of navel orange is larger, with better red, the difference of color is mainly related to the carotene contained in the fruit.

Table 7. Comparison of nutritional indexes of navel orange and summer orange by microwave treatment.

Treatment	Navel orange		Summer orange	
	Before sterilization	After sterilization	Before sterilization	After sterilization
SSC ($^{\circ}\text{Brix}$)	12.8 \pm 0.1	12.6 \pm 0.2	10.2 \pm 0.2	10.0 \pm 0.2
TA (mg/100 mL)	7.6 \pm 0.1	7.4 \pm 0.1	15.5 \pm 0.2	15.4 \pm 0.1
Vc (mg/100 mL)	42.0 \pm 2.0	35.1 \pm 2.0	40.6 \pm 2.1	33.3 \pm 1.5
Hardness (g)	113 \pm 3.0	115 \pm 3.0	115 \pm 2.0	125 \pm 2.10
Color difference (L^*)	40.2 \pm 0.1	42.3 \pm 0.3	45.5 \pm 0.4	48.7 \pm 0.4
Color difference (a^*)	3.2 \pm 0.3	2.6 \pm 0.1	2.5 \pm 0.2	2.0 \pm 0.2
Color difference (b^*)	25.2 \pm 0.7	26.1 \pm 0.3	21.2 \pm 0.3	22.0 \pm 0.1

4. Conclusion

The best conditions of microwave sterilization are power 6kw, microwave sterilization time 350s and material quantity 4500g. Compared with thermal sterilization, microwave sterilization is safe and efficient. It can be completed in 350s and meet the requirements of relevant health indicators. It not only consumes less energy than thermal sterilization, but also has less impact on color. What's more, the industrialization of microwave continuous treatment related equipment is mature, which has the basic conditions to promote the application to the industry, and has the potential to replace the traditional thermal sterilization of the factory. The nutritional indexes of different varieties (navel

orange and summer orange) changed after microwave sterilization. Compared with the nutritional indexes of navel orange and summer orange, it was found that the content of soluble solids of navel orange was higher, the color a^* was larger, and the acidity was suitable. Compared with summer orange, navel orange is more suitable for juice processing.

Acknowledgement

This research was supported by National Key R&D Plan (2017YFD0400701) and School Local Cooperation Project (4411901868), China.

References

- [1] S. Wibowo, T. Grauwet, B.T. Kebede, et al, Food Res. Int. **75**, 295-304 (2015).
- [2] S. Aghajanzadeh, A.M. Ziaifar, M. Kashaninejad, et al, J. Food Eng. **185**, 72-77 (2016)
- [3] E.A. Baldwin, J.H. Bai, A. Plotto, et al, J. Sci. Food Agri. **92**, 2029-2042 (2012)
- [4] Z.Z. Xu, T.T. Lin, Y.T. Wang, et al, Innov. Food Sci. Emerg. **31**, 28-36 (2015)
- [5] I.S. Woo, I.K. Rhee, H.D. Park, Appl. Environ. Microbiol. **66**, 2243-2247 (2000)
- [6] S.M. Hong, J.K. Park, Y.O. Lee, Water Res. **38**, 1615-1625 (2004)
- [7] M. Porcelli, G. Cacciapuoti, S. Fusco, et al, Febs Lett. **402**, 102-106 (1997)
- [8] A. Shaman, S. Mizrahi, U. Cogan, et al, Food Chem, **103**, 444-453 (2007)
- [9] M. Ballardín, I. Tusa, N. Fontana, et al, Mut. Res. Fund. Mol. Mech. Mut. **716**, 1-9 (2011)
- [10] A.M. Phelan, C.F. Neubauer, R. Timm, et al, Radiat. Res. **137**, 52-58 (1994)
- [11] Y.L. Zhao, H.B. Ma, J.P. Song, et al, Space Med. Med. Eng. (Beijing) **16**, 36-40 (2003)
- [12] P. Coronel, J. Simunovic, K.P. Sandeep, et al, J. Food Eng. **85**, 528-536 (2008)
- [13] R. Vadivambal, D.S. Jayas, Food Bioprocess Tech. **3**, 161-171 (2010)
- [14] C. Salazar-Gonzalez, M.F. San Martín-Gonzalez, A. Lopez-Malo, et al, Food Food Bioprocess Tech. **5**, 31-46 (2012)